

Product data sheet

Specifications



PratiKa Unika - mounting box - 16-32 A - with undermade walls

83919

Main

Product or component type	Mounting box
---------------------------	--------------

Complementary

Enclosure mounting	Wall mounted
Number of horizontal rows	0
[In] rated current	32 A 16 A
Type of rail	DIN
Cable entry	: smooth faces
Enclosure material	Housing: self-extinguishing polymer
Net weight	0.308 kg
Base dimension	103 x 225 mm
Width	103 mm
Height	250 mm
Depth	70 mm
Colour	Housing: light grey (RAL 7035)

Environment

Standards	IEC 309-2 EN 60309-2 IEC 60529 EN 62262 IEC 309-1 EN 60439-1 IEC 695-2-1 EN 60309-1
Fire resistance	750 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristics (UV)	UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013
Ambient air temperature for operation	-25...40 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.0 cm
Package 1 Width	10.3 cm
Package 1 Length	24.5 cm
Package 1 Weight	356.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	8
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.35 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)