



KCF2-25



KCF14-85



PVCF10



PVCF14-85

Fuse holder 1000V DC

KCF2-25

- No.of pole: 1P,2P,3P,4P

-Rated voltage: 1000V DC

-Rated current: 25A

-Utilization category: DC-20B or AC-20B
- Rated insulation voltage: 1100V

-Rated impulse withstand voltage: 6kV

-Comply with IEC60947

Description	cat.nos.	fuse link size	pack	carton
1 pole	856 01	10X38mm	12	240
2 pole	856 02	10X38mm	6	120
3 pole	856 03	10X38mm	4	80
4 pole	856 04	10X38mm	3	60

Fuse holder 1500V DC

KCF14-85

- Rated voltage:1500V DC

-Rated current:32A

-Rated impulse withstand voltage:20kV

-Utilization category: DC-20B or AC-20B
- Wire range:2.5-16mm2

-Torque:2...2.5Nm

-Comply with IEC60269-6

Description	cat.nos.	fuse link size	pack	carton
1 pole	856 21	10X85mm	5	90

Fuse link 1000V DC

PVCF10

- Rated voltage: 1000V DC

-Rated current: 1-25A

-Rated breaking capacity : 25kA
- Class: gPV

-Comply with IEC60269-6

Description	cat.nos.	size	pack	carton
1A	857 01	10X38mm	10	1000
2A	857 02	10X38mm	10	1000
3A	857 03	10X38mm	10	1000
4A	857 04	10X38mm	10	1000
5A	857 05	10X38mm	10	1000
6A	857 06	10X38mm	10	1000
8A	857 07	10X38mm	10	1000
10A	857 08	10X38mm	10	1000
12A	857 09	10X38mm	10	1000
15A	857 10	10X38mm	10	1000
20A	857 11	10X38mm	10	1000
25A	857 12	10X38mm	10	1000

Fuse link 1500V DC

PVCF14-85

- Rated voltage:1500V DC

-Rated current:2-20A


-Rated breaking capacity :20KA
- Class: gPV

-Comply with IEC60269-6

Description	cat.nos.	size	pack	carton
2A	857 21	10X85mm	10	1000
3A	857 22	10X85mm	10	1000
4A	857 23	10X85mm	10	1000
5A	857 24	10X85mm	10	1000
6A	857 25	10X85mm	10	1000
8A	857 26	10X85mm	10	1000
10A	857 27	10X85mm	10	1000
12A	857 28	10X85mm	10	1000
15A	857 29	10X85mm	10	1000
20A	857 30	10X85mm	10	1000
25A	857 31	10X85mm	10	1000
32A	857 32	10X85mm	10	1000




KCD10 1P



DC 250V (1P)



KCD10 2P



DC 500V (2P)

Mini circuit breaker 1000V DC

KCD10

- No.of pole: 1P

-Rated voltage: 250V DC

-Comply with IEC60947-2
- Rated insulation voltage: 1000V

-Rated impulse withstand voltage: 6kV

-Rated short-circuit breaking capacity: 10kA

Description	B curve	C curve	pack	carton
1 pole 1 A 250VDC	262 01	262 21	12	120
1 pole 2 A 250VDC	262 02	262 22	12	120
1 pole 3 A 250VDC	262 03	262 23	12	120
1 pole 4 A 250VDC	262 04	262 24	12	120
1 pole 6 A 250VDC	262 05	262 25	12	120
1 pole 10 A 250VDC	262 06	262 26	12	120
1 pole 16 A 250VDC	262 07	262 27	12	120
1 pole 20 A 250VDC	262 08	262 28	12	120
1 pole 25 A 250VDC	262 09	262 29	12	120
1 pole 32 A 250VDC	262 10	262 30	12	120
1 pole 40 A 250VDC	262 11	262 31	12	120
1 pole 50 A 250VDC	262 12	262 32	12	120
1 pole 63 A 250VDC	262 13	262 33	12	120

Mini circuit breaker 1000V DC

KCD10

- No.of pole: 2P

-Rated voltage: 500V DC

-Comply with IEC60947-2
- Rated insulation voltage: 1000V

-Rated impulse withstand voltage: 6kV

-Rated short-circuit breaking capacity: 10kA

Description	B curve	C curve	pack	carton
2 pole 1 A 500VDC	262 41	262 61	6	60
2 pole 2 A 500VDC	262 42	262 62	6	60
2 pole 3 A 500VDC	262 43	262 63	6	60
2 pole 4 A 500VDC	262 44	262 64	6	60
2 pole 6 A 500VDC	262 45	262 65	6	60
2 pole 10 A 500VDC	262 46	262 66	6	60
2 pole 16 A 500VDC	262 47	262 67	6	60
2 pole 20 A 500VDC	262 48	262 68	6	60
2 pole 25 A 500VDC	262 49	262 69	6	60
2 pole 32 A 500VDC	262 50	262 70	6	60
2 pole 40 A 500VDC	262 51	262 71	6	60
2 pole 50 A 500VDC	262 52	262 72	6	60
2 pole 63 A 500VDC	262 53	262 73	6	60