

# Product data sheet

Specifications



## Asfora - single socket outlet with pin earth - 16A lid, shutters IP44 white

EPH2800321

### Main

|                               |                      |
|-------------------------------|----------------------|
| Range                         | Asfora               |
| Product or component type     | Socket-outlet        |
| Outlet standard description   | Pin earth            |
| Outlet poles configuration    | 2P + E with shutters |
| Device presentation           | Complete product     |
| Socket additional information | Lid and shuttered    |
| Colour tint                   | White                |
| Type of packing               | Flow-pack            |

### Complementary

|                         |   |
|-------------------------|---|
| Socket number           | 1   |
| Device mounting         | Flush   |
| Power range             | 3680 W  |
| Rated current           | 16 A at 250 V AC  |
| Connections - terminals | Lift terminals  |
| Number of cables        | 2 cable(s) 2.5 mm²  |
| Cable stiffness         | Flexible<br>Rigid<br>Solid stranded   |
| Wire stripping length   | 13.0 mm   |
| Material                | ABS (acrylonitrile butadiene-styrene): cover frame<br>ABS + PC: central plate<br>ABS (acrylonitrile butadiene-styrene): lid |
| Surface finish          | Glossy  |
| Conductor material      | Copper  |
| Fixing mode             | Screws or claws51...69 mm   |
| Height                  | 83 mm   |
| Width                   | 83 mm   |
| Depth                   | 48 mm   |
| Projecting depth        | 17 mm   |
| Quantity per set        | 1   |

|            |          |
|------------|----------|
| Net weight | 0.086 kg |
|------------|----------|

### Environment

|                         |                |
|-------------------------|----------------|
| Standards               | IEC 60884-1    |
| Product certifications  | SEP-BBJ<br>TSE |
| IP degree of protection | IP44           |

### Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Weight             | 107.85 g  |
| Package 1 Height             | 4.5 cm    |
| Package 1 width              | 8.5 cm    |
| Package 1 Length             | 8.5 cm    |
| Unit Type of Package 2       | BB1       |
| Number of Units in Package 2 | 10        |
| Package 2 Weight             | 1.152 kg  |
| Package 2 Height             | 9.5 cm    |
| Package 2 width              | 18.5 cm   |
| Package 2 Length             | 27.5 cm   |
| Unit Type of Package 3       | S04       |
| Number of Units in Package 3 | 120       |
| Package 3 Weight             | 14.459 kg |
| Package 3 Height             | 30 cm     |
| Package 3 width              | 40 cm     |
| Package 3 Length             | 60 cm     |

### Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information       |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|