

# Product data sheet

Specifications



## Pragma surface enclosure - IP30 - 3 x 13 modules - without door

PRA13653

### Main

Range	Pragma
Product or component type	Enclosure
Enclosure type	Distribution enclosure
Width	336 mm
Height	600 mm
Depth	123 mm
Nb of 18 mm modules per row	13
Nb of horizontal rows	3
Electrical insulation class	Class II Double insulation
Provided equipment	1 x identification label 1 x marking kit 1 x blanking plate strip 3 x terminal block
Type of door	Without

### Complementary

Enclosure mounting	Surface
9 mm pitches	26
Total number of 18 mm modules	39
Power dissipation in W	45 W
[In] rated current	90 A
Type of rail	DIN
Cable entry	Cut-out plates Cable or tube Trunking Removable plates
Comb busbar and distribution block compatibility	XE compatible
Number of terminal blocks	1 earth (Quick) with 29 outgoers 2 phase / neutral (Quick) with 7 outgoers
Distribution block outgoers	4 x 25 mm <sup>2</sup> for earth 25 x 4 mm <sup>2</sup> for earth 2 x 35 mm <sup>2</sup> for phase / neutral 12 x 16 mm <sup>2</sup> for phase / neutral
Enclosure material	Back part: technoplastic

Front face: technoplastic

**Colour** Enclosure: white (RAL 9016)  
Front face: white (RAL 9016)

**Targeted country** France

## Environment

**Fire resistance** Back part: 750 °C  
Front face: 750 °C

**IP degree of protection** IP30 without door  
IP40 with door

**IK degree of protection** IK08 without door  
IK09 with door

**Overvoltage category** II

**Ambient air temperature for operation** -25...60 °C

**Standards** IEC 60670-1  
IEC 60670-24  
IEC 61439-1  
IEC 61439-3

## Packing Units

**Unit Type of Package 1** PCE

**Number of Units in Package 1** 1

**Package 1 Weight** 3.9 kg

**Package 1 Height** 13.5 cm

**Package 1 width** 42 cm

**Package 1 Length** 68 cm

**Unit Type of Package 2** P12

**Number of Units in Package 2** 21

**Package 2 Weight** 105.87 kg

**Package 2 Height** 120 cm

**Package 2 width** 80 cm

**Package 2 Length** 120 cm

## Offer Sustainability

**Sustainable offer status** Green Premium product

**REACH Regulation** [REACH Declaration](#)

**REACH free of SVHC** Yes

**EU RoHS Directive** Pro-active compliance (Product out of EU RoHS legal scope)  
[EU RoHS Declaration](#)

**Toxic heavy metal free** Yes

**Mercury free** Yes

**RoHS exemption information** [Yes](#)

**China RoHS Regulation** [China RoHS declaration](#)  
Pro-active China RoHS declaration (out of China RoHS legal scope)

**Environmental Disclosure** [Product Environmental Profile](#)

## Contractual warranty

**Warranty** 18 months